



# Educator 25" School Laminator

**Easy to use...Reliable...Great Value...  
Low Maintenance**

Before designing this machine, we asked teachers and media specialists what they wanted in a laminator. They told us ease of use, reliability, value, and low maintenance. That's what we designed into the Educator.

We started with our best all-around laminator, simplified the controls, and created an improved film path to eliminate many of the operator errors common to other thermal laminators.

Posters, dry erase charts, flash cards, bulletin board graphics, games, visuals, and teaching aids of all kinds represent a tremendous investment, whether they were purchased or made by teachers. Protecting and enhancing these educational materials with lamination allows them to last for years instead of being replaced every few weeks or months. The Educator offers the control needed to laminate different types of material using a variety of films with a minimum of operator adjustments.

An instructional video and operations manual are shipped with every Educator.

Features that contribute to the quality of lamination and dependability of the Educator include:

- **Preset lamination pressure and speed** make the machine easier to use and eliminate potential sources of problems.
- **Enclosed laminating and pull rollers** help avoid time consuming jams and wrap-arounds.
- **Forced air cooling** allows laminating with 3 and 5 mil films, as well as the 1.5 mil film often used by schools. Without a film cooling system, thicker films would warp and ripple because they would be too hot and still in the process of setting up when they exited the laminator.
- **Fixed-position lamination rollers** provide a stable platform for uniform roll pressure to ensure high-quality lamination.
- **Attached safety shield** is fixed to the machine and is placed so that the operator will naturally put it in the guard position before laminating. The shield is made of clear polycarbonate so users can

see their work and will not be tempted to try to laminate without the shield in the safe position.

- **Reverse switch** is invaluable to help avoid problems or clear misfeeds.
- **Adjustable heat control** allows the use of films up to 5 mils thick. It's as easy to use as an oven dial.
- **Supply roll tension** knobs provide the control needed to get wrinkle-free lamination without complicating your work.
- **Separate safety cutter** provides a safe means of cutting work off the back of the machine. This eliminates the usual tear bar which may cut fingers or snag clothing.
- **Made in the U.S.A.** means quality, better service, and faster parts availability.
- **Two-year manufacturers parts and labor warranty.**



# The Educator 25" School Laminator

## A ROLL LAMINATOR DESIGNED AND MANUFACTURED EXCLUSIVELY FOR SCHOOLS. OPTIONS

The **Footage Counter** can be set to accurately measure film usage; available in U.S. standard or metric.

The **Slitter Assembly** will trim side scrap from your work with a high degree of precision. The slitter includes two cutting heads. The blades are fully retractable for safety.

The **Dust Cover** will help keep the machine clean while not in use.

A **Right Side Feed Guide** is available for those who want greater feeding precision.

### You can preserve and protect:

- |                 |                     |
|-----------------|---------------------|
| Teaching Aids   | Presentations       |
| ID Cards/Badges | Posters             |
| Art Work        | Charts              |
| Flash Cards     | Menus               |
| Visuals         | Name Tags           |
| Awards          | Certificates        |
| Games           | Price Lists         |
| Photographs     | Sales Aids          |
| Recipes         | POP Displays        |
| Memorabilia     | Instructional Mat'l |
| Book Jackets    | Safety Warnings     |
| Place Mats      | Membership Cards    |
| Luggage Tags    | News Clippings      |
| Licenses        | Public Notices      |
| Reports         | Promotional Items   |
| Bookmarks       | Dry Erase Charts    |
| Signs           | Spec Sheets         |
| Maps            | Flyers              |

## SPECIFICATIONS

Maximum Laminating Width .....	Up to 25"
Dimensions .....	32L" x 11H" x 16D"
Shipping Dimensions .....	37L" x 17H" x 18D"
Weight/Shipping Weight .....	76/84 lbs.
Speed .....	5 feet per minute
Electrical .....	110V (220V optional) 1500 watts, 15 amps
Lam Roll Diameter .....	1-1/4"
Max Film Gauge .....	5 mil
Max Laminating Thickness .....	1/8"
Max Film Roll Diameter .....	6"
Lam. Roll Diameter .....	1-1/4"
Film Core Size .....	1"
Max Film Capacity with 1.5 mil .....	500 feet
with 3 mil .....	250 feet

Member:



# LEDCO INC.

LAMINATION TECHNOLOGY  
1525 AIRPORT ROAD  
CONROE, TEXAS 77301  
PHONE: (936) 539-4461  
TOLL FREE: (877) 544-6448  
FAX: (936) 539-6090